




Gorilla Grade 80 component couplers are manufactured to AS3776 and are commonly used to connect head rings, chain, hooks and other lifting components.



SCAN QR CODE
FOR ASSEMBLY
INSTRUCTIONS

| Picture | Model | Size | Chain Size (mm) | W.L.L (T) | b (mm) | c (mm) | e (mm) | g (mm) | d (mm) | s (mm) | N.W. (kg) |
|--|-----------|---------|-----------------|-----------|--------|--------|--------|--------|--------|--------|-----------|
|  | LG-CC-T06 | 6-8 | 6 | 1.1 | 40 | 7 | 45 | 18 | 7.7 | 10.5 | 0.07 |
| | LG-CC-T08 | 7/8-8 | 7-8 | 2 | 49.5 | 10.2 | 57 | 19 | 9.3 | 15.2 | 0.15 |
| | LG-CC-T10 | 10-8 | 10 | 3.2 | 63 | 12 | 73 | 27 | 12.9 | 17.2 | 0.35 |
| | LG-CC-T13 | 13-8 | 13 | 5.3 | 82 | 16 | 88 | 34 | 16.8 | 22.7 | 0.68 |
| | LG-CC-T16 | 16-8 | 16 | 8 | 105 | 19 | 103 | 39 | 20.6 | 28 | 1.1 |
| | LG-CC-T20 | 18/20-8 | 20 | 12.5 | 122 | 23.5 | 116 | 47 | 25.8 | 34.8 | 2.2 |